

CLAIMS:

1. A multi-piece solid golf ball comprising a solid core
and a cover of two inner and outer layers surrounding the
5 core, the outer cover layer having a surface formed with a
plurality of dimples, characterized in that
a product of the Shore D hardness of said inner cover
layer multiplied by the Shore D hardness of said outer
cover layer and a proportion V_R (%) of the total of the
10 volumes of dimple spaces each defined below a plane
circumscribed by the dimple edge to the overall volume of
a phantom sphere given on the assumption that the golf
ball surface is free of dimples satisfy any one of the
following combinations (1) to (5):
15 (1) the product of Shore D hardnesses of inner and outer
cover layers: 1,500 to less than 2,000
 V_R : 0.8 to 1.1%
(2) the product of Shore D hardnesses of inner and outer
cover layers: 2,000 to less than 2,500
20 V_R : 0.75 to 1.05%
(3) the product of Shore D hardnesses of inner and outer
cover layers: 2,500 to less than 3,000
 V_R : 0.7 to 1%
(4) the product of Shore D hardnesses of inner and outer
25 cover layers: 3,000 to less than 3,500
 V_R : 0.65 to 0.95%
(5) the product of Shore D hardnesses of inner and outer
cover layers: 3,500 to 4,000
 V_R : 0.6 to 0.9%,
30 and said dimples include at least three types of dimples
which are different in at least one of a diameter, a
depth, and a value V_0 which is the volume of one dimple
space defined below a plane circumscribed by the dimple
edge divided by the volume of a cylinder whose bottom is
35 the plane and whose height is the maximum depth of the
dimple from the bottom.

2. The multi-piece solid golf ball of claim 1 wherein the solid core has a distortion of 2.6 to 6.5 mm under an applied load of 100 kg.

5 3. The multi-piece solid golf ball of claim ~~1 or 2~~¹ wherein both the hardnesses of the inner and outer cover layers are up to 63 in Shore D hardness.

add B1
add C1

[illegible]